

Intended Use

- For the repair of polishable natural stone (not sand-stone, or porous limestone) and diverse engineered stones.
- Construction system especially for vertical surface damages.
- To be used solely or in combination with other filler materials from the RepairLux[®] range.
- For indoor and outdoor use.

Characteristics

- A light-hardening filler material (LED).
- Cures in coats up to 3 mm.
- A thixotropic paste.
- Clear transparent.
- Planable, sandable and polishable.
- High stability and resistance.
- Lightfast.
- Weather resistant.

Application Notes

Ensure processing temperature is above +8°C (filler and surface). Do not apply in direct sunlight. Clean damaged area from dirt and loose particles using auxiliaries from the system. Fill damage in stages of 3 mm maximum and cure each coat individually. To imitate a crystalline structure and shadings, the filler can be combined with relevant Granulates (fine and coarse art.no. 403 020-025) and Colours (art.no. 403 006-019). To achieve best results apply a final coat of RepairLux[®] Transparent Liquid.

In case of damage on edges build up the edge with RepairLux[®] Transparent Base. Thanks to its good stability, the filler can be molded in. If necessary, create a kind of formwork with transparent adhesive tape (Sellotape) and cover the repair with RepairLux[®] Transparent Liquid. Strip off excess material with the Planer. Finally, adjust the gloss level using Micro Sanding Paper and Polishing Paste.

For detailed description of the individual system components and their use, please refer to the instructions for use.

Physical Properties and Shelf Life

Curing period:	30 secs/cm ²
Curing layer:	3 mm max. (construction)
Temperature resistance:	up to 150°C for short periods
Shelf life:	minimum 2 years (stored in unopened original container and lightproof at 12-28°C)

Safety Precautions

Please refer to label and material safety data sheet.

Disposal

- Dispose of leftover material and completely empty containers in accordance with legal requirements. For further information, please ask your local waste industry office.
- Cured product is an inert plastic material, which can be disposed of in compliance with official regulations.
- European Waste Code for uncured material: 080409.

Packaging

3ml syringes

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

Issue 37/16