

Uses

- To maintain glazed wooden windows and foil-covered plastic windows.
- Provides a new sheen to window frames and prolongs maintenance intervals.
- Application every six months is recommended.
- For indoor and outdoor use.

Characteristics

- A physically drying lacquer based on water.
- Easy to apply.
- Dries rapidly.
- UV-protection, will not yellow.
- Soil-resistant and water-repellent protective coating.
- Gloss level: silk gloss.

Application

Shake container well before use. Surface has to be dry and free of grease. If necessary, clean with Eco-Cleaner 516. Check compatibility on an inconspicuous area, first. Do not use Universal Maintenance Lacquer in direct sunlight or on surfaces that are heated up. Processing temperature 12-25°C.

Pour Maintenance Lacquer into a flat bowl, soak Maintenance Sponge or sponge cloth and spread Maintenance Lacquer extensively. Strip off sparsely just once lengthwise, do not polish.

After a few minutes the treated area will be dry and after approx. 30 minutes hard-wearing. Wash out Maintenance Sponge/sponge cloth with water after use.

Specifications

Character: dispersion lacquer, watery.
Dust-dry: after approx. 5-10 minutes.
Hard-wearing: after approx. 30 minutes.
Coverage: approx. 2-4 m² per 200 ml (single application).

Light- and weather resistance: good.
Water resistance: very good.
Adhesion: very good.
Elasticity: very good.
Shelf life: at least 1 year
 (stored upright at room temperature, in original unopened container).

Protect from frost!

Safety Precautions

- Keep out of reach of children.
- In case of contact with eyes rinse immediately with plenty of water.

Extract of wordings of the law. For further information please see label and Material Safety Data Sheet.

Disposal

- Container to be added to the household waste, only when completely emptied and dried-out.
- Material leftovers to be disposed of according to the European Waste Code 080120 – *aqueous suspensions containing paint or varnish other than those mentioned in 080119.*


Packaging

Container size: 1000 ml

For resale to enduser:
 200 ml 'Quick & Clean'
customised labelling possible

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01 - 53 60 0 • Fax: 0 61 01 - 53 60 11

E-mail: info@heinrich-koenig.de

Issue 11/05