

# König Graining Pen 205 000

## Uses

- For the glazing tracing of fine wood grains/structures.
- Recommended for indoor use.

## Characteristics

- Dries rapidly.
- Resists water and wiping.
- Good adhesion to varnished and wooden surfaces that are free from dust and grease.
- Can be varnished with all König clear lacquers.
- Application without lacquer formation, ideal for precise touch-up work (fine strokes and dots).
- Non-refillable.
- Produced on solvent-base.

## Application

Remove cap – pen is immediately ready for use.  
Dab on glaze with the tip of the pen as much as required – using no pressure – or apply with short strokes.  
If too much glaze has been applied and therefore the application becomes too dark, it can be toned down with wire wool after it has begun to dry.  
In case of 'strongly soaking', untreated or raw wood (e.g. abraded areas) just dab on slightly.  
When repairing filled spots (e.g. with König fillers) apply a barrier coat with Special Repair Lacquer PLUS to the ground underneath. To obtain a final sealing, spray again with Special Repair Lacquer PLUS.  
From time to time clean the brush tip with a cloth to avoid contamination.  
Prevent the brush tip coming into contact with lacquers, e.g. when retouching-up lacquers that have not completely dried. The tip might become sticky or resinous.  
Close pen carefully after use – danger of drying up!

## Specifications

|                               |                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Dust-dry:</b>              | after 1-2 minutes.                                                                               |
| <b>Touch-dry:</b>             | after approx. 5 minutes<br>(dependent on room temperature and coat thickness).                   |
| <b>Water resistance:</b>      | good.                                                                                            |
| <b>Adhesion:</b>              | very good, except to PE/PP, limited adhesion to UV-hardened lacquer systems and powder lacquers. |
| <b>Can be lacquered over:</b> | unproblematically – as far as known.                                                             |
| <b>Shelf life:</b>            | 1 year minimum<br>(stored at room temperature, in original unopened container)                   |

## Safety Precautions

- Keep out of reach of children.

*Extract of wordings of the law. For further information please see label and Material Safety Data Sheet.*

## Disposal


- Do not allow product to enter drains or watercourses.
- Pen to be added to the household waste only, when completely emptied and dried-out.
- Material leftovers to be disposed of according to the European Waste Code 080111 – *waste paint and varnish containing organic solvents or other dangerous substances.*

## Packaging

Assortment of 10  
Standard and special colour shades (S.A.)

*Further information and Material Safety Data Sheet on the internet at  
[www.heinrich-koenig.de](http://www.heinrich-koenig.de)*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



**Heinrich König & Co. KG**

An der Rosenhelle 5 • D-61138 Niederdorfelden  
Phone 2 0 61 01 - 53 60 0 • Fax: 0 61 01 - 53 60 11  
E-mail: [info@heinrich-koenig.de](mailto:info@heinrich-koenig.de)

Issue 33/02