

Intended Use

- To be used on lacquer, décor and laminate surfaces.
- For a spraying without lacquer formation to small partial surfaces.
- For sheen level adjustment.
- For the sealing of repaired damages.
- Recommended for indoor use.

Characteristics

- A transparent combination lacquer based on nitrocellulose.
- Free from formaldehyde and aromatic substances.
- Good steam resistance.
- Dust-dry after approx. 5-10 minutes – dries to the touch in about 20 minutes.
- To be used to create very thin coats.
- Good adhesion properties.
- Good mechanical and chemical resistance.

Application Notes

Shake can well before use and briefly spray valve free. Check compatibility and adhesion on an inconspicuous area first.

Surface must be clean and free of grease. If necessary, make a pre-treatment (sand slightly and remove sanding dust).

Just spray on thin coats of lacquer from a distance of approx. 40-50 cm.

Allow lacquer to dry for approx. 20 minutes between each work step.

When sealing a repair with touch-up colours these will turn 'brighter' for a short while – as soon as lacquer has dried the original colour shade will return.

In case of vertical surfaces, several thin coats are best. Allow for a 10 minutes flash-off time between each coat.

Physical Properties and Shelf Life

Dust-dry:	after 5-10 minutes
Touch-proof:	after 20 minutes
Hard cured:	after 7 days
Resistance:	PVC-resistant
DIN 68861-1B:	chemical resistance
DIN 4102-B2:	not easily inflammable
Levelling:	good
Light resistance:	good
Shelf life:	minimum 2 years (stored upright at room temperature, in unopened original container)

Safety Precautions

- Extremely flammable.
- Pressurized container.
- Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Do not spray on a naked flame or any incandescent material.
- Keep away from sources of ignition – No smoking.
- Do not spray into eyes.
- Keep out of reach of children.

Extract of wordings of the law. For further information, please see label and Material Safety Data Sheet.

Disposal


- Dispose of König aerosol cans in accordance with legal requirements only, when completely empty. For further information, please ask your local waste industry office.
- Leftover material to be disposed of according to the European Waste Code 160505 – *gases in pressure containers other than those mentioned in 160504.*
- Heinrich König & Co. KG take care of the disposal of Sprüh-König aerosol cans, provided they are returned 'carriage paid' to the address stated below.

Packaging

150 ml/400 ml Sprüh-König aerosol can
Sheen levels: deep matt, matt, silk matt, silk gloss, gloss

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

Issue 15/03